


## Synthetic cable collector Multi with conduit connector



### Synthetic cable collector ROHRflex® PA 6 Multi

- ROHRflex® PA 6 Multi
- Grey

|                        |                                                                                                                                  |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>     | <b>0206.201.095</b>                                                                                                              |
| EAN:                   | 7611614013336                                                                                                                    |
| Material               | Polyamide PA 6                                                                                                                   |
| Fire classification    | HB (UL 94)                                                                                                                       |
| Properties             | Non-crush, liquid-tight, oil resistant up to +80°C, petrol resistant, basically resistant to acids and solvents, flame retardant |
| Application            | Machine and plant constructions, vehicle construction, shipbuilding, automation, electrical installations                        |
| Protection class       | IP 68 / IP 69                                                                                                                    |
| Operation temperature  | -40°C / +120°C / ^ +150°C                                                                                                        |
| Outer diameter         | 95 mm                                                                                                                            |
| Diameter A             | 106.0 mm                                                                                                                         |
| Inner diameter         | 91.0 mm                                                                                                                          |
| Bending radius static  | 225 mm                                                                                                                           |
| Bending radius dynamic | 450 mm                                                                                                                           |
| Dispatch               | 10                                                                                                                               |