


## Synthetic protective conduits ROHRflex® PA 6



EN 45545-2

HL 3



### Synthetic protective conduits ROHRflex® PA 6-D

- ROHRflex® PA 6-D
- Black

|                        |                                                                                                                                                                                                                                                                |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article no:            | 0237.202.023                                                                                                                                                                                                                                                   |
| E-No:                  | 125192500                                                                                                                                                                                                                                                      |
| EAN:                   | 7611614092799                                                                                                                                                                                                                                                  |
| Material               | Polyamide PA 6                                                                                                                                                                                                                                                 |
| Fire classification    | V0 (UL 94)                                                                                                                                                                                                                                                     |
| Properties             | Strong version with enhanced lateral compressive strength, air- and liquid-tight, oil resistant up to +80°C, petrol resistant, basically resistant to acids and solvents, free of silicone, free of cadmium, halogen-free, self extinguishing, black tubing is |
| Application            | Machine and plant constructions, vehicle construction, rail vehicles inside applications, shipbuilding, automation, electrical installations                                                                                                                   |
| Protection class       | IP 68 / IP 69                                                                                                                                                                                                                                                  |
| Operation temperature  | -40°C / +120°C / ^ +150°C                                                                                                                                                                                                                                      |
| Outer diameter         | 28.5 mm                                                                                                                                                                                                                                                        |
| Inner diameter         | 22.5 mm                                                                                                                                                                                                                                                        |
| Bending radius static  | 60 mm                                                                                                                                                                                                                                                          |
| Bending radius dynamic | 100 mm                                                                                                                                                                                                                                                         |
| Dispatch               | 50                                                                                                                                                                                                                                                             |