


## Synthetic protective conduits ROHRflex® PA 6



### Synthetic protective conduits ROHRflex® PA 6-LB

- ROHRflex® PA 6-LB
- Black

|                        |                                                                                                                                                                                            |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>     | <b>0261.232.048</b>                                                                                                                                                                        |
| E-No:                  | 125216800                                                                                                                                                                                  |
| EAN:                   | 7611614170312                                                                                                                                                                              |
| Material               | Polyamide PA 6                                                                                                                                                                             |
| Fire classification    | HB (UL 94)                                                                                                                                                                                 |
| Properties             | Air- and liquid-tight, oil-resistant up to +80°C, petrol-resistant, largely acid- and solvent-resistant, silicone- and cadmium-free, halogen-free, flame-retardant. UV-resistant in black. |
| Application            | Window and facade construction, mechanical and plant constructions, automotive, shipbuilding, automation, electrical systems                                                               |
| Protection class       | IP 68                                                                                                                                                                                      |
| Operation temperature  | -25°C / +120°C                                                                                                                                                                             |
| Outer diameter         | 54.5 mm                                                                                                                                                                                    |
| Inner diameter         | 47.0 mm                                                                                                                                                                                    |
| Bending radius static  | 100 mm                                                                                                                                                                                     |
| Bending radius dynamic | 190 mm                                                                                                                                                                                     |
| Dispatch               | 25                                                                                                                                                                                         |