


## Synthetic protective conduits ROHRflex® PU



UK  
CA

### Synthetic protective conduits ROHRflex® PU

- ROHRflex® PU
- Black

|                        |                                                                                                                                                                                                                                           |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>     | <b>0289.932.016</b>                                                                                                                                                                                                                       |
| EAN:                   | 7611614151274                                                                                                                                                                                                                             |
| Material               | Polyurethane                                                                                                                                                                                                                              |
| Fire classification    | HB (UL 94)                                                                                                                                                                                                                                |
| Properties             | Airtight and waterproof, resistant to oil, petrol and fats, widely resistant to acids and solvents, free of silicone, cadmium and halogen, elevated tenacity and resistance to abrasion, very flexible, resistant to microbes and UV rays |
| Application            | Machine and plant constructions, vehicle construction, shipbuilding, automation, electrical installations                                                                                                                                 |
| Protection class       | IP 68 / IP 69                                                                                                                                                                                                                             |
| Operation temperature  | -40°C / +120°C                                                                                                                                                                                                                            |
| Outer diameter         | 21.2 mm                                                                                                                                                                                                                                   |
| Inner diameter         | 15.2 mm                                                                                                                                                                                                                                   |
| Bending radius static  | 35 mm                                                                                                                                                                                                                                     |
| Bending radius dynamic | 75 mm                                                                                                                                                                                                                                     |
| Dispatch               | 50                                                                                                                                                                                                                                        |