


## Conduit glands for Liquid-tight conduit



### Complete conduit gland nickel-plated brass

- Conduit gland EG-M
- for LIQUID-TIGHT protective conduits
- LIQUID-TIGHT-UL / CSA / -EF

|                       |                                                                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>0608.000.025</b>                                                                                                                                |
| EAN:                  | 7611614157702                                                                                                                                      |
| Material              | Nickel-plated brass                                                                                                                                |
| Sealing ring          | Polyamide PA 6                                                                                                                                     |
| Properties            | Highly watertight and dustproof, friction locking of conduit and gland, proper earthing, covered conduit ends, resistant to stretch and vibrations |
| Application           | Installation according to US and Canadian specifications, for use in machinery and installations                                                   |
| Protection class      | IP 67                                                                                                                                              |
| Operation temperature | -45°C / +105°C                                                                                                                                     |
| Outer diameter        | 3/4" mm                                                                                                                                            |
| Entry thread          | M25x1.5                                                                                                                                            |
| Inner diameter        | 21.0 mm                                                                                                                                            |
| Diameter A            | 26.5 mm                                                                                                                                            |
| Diameter Ø B          | 18.5 mm                                                                                                                                            |
| Dimension C           | 15 mm                                                                                                                                              |
| Wrench size 1         | 35                                                                                                                                                 |
| Wrench size 2         | 33                                                                                                                                                 |
| Dispatch              | 5                                                                                                                                                  |

The protection class of the conduit fitting depends on the selection of the type of conduit