


Cable glands Progress® nickel-plated brass with antikink spring



Short entry thread metric

Type approval: Progress MS FKN

- One-piece sealing insert
- overall length insulated

| | |
|-----------------------|------------------------------|
| Article no: | 1060.12.52.065 |
| E-No: | 121783318 |
| EAN: | 7611614195117 |
| Material | Nickel-plated brass |
| Antikink spring | Stainless steel A2 |
| Seal | TPE |
| O-ring | NBR |
| Operation temperature | -40°C / +100°C |
| Strain relief | Version A acc. to EN 62444 |
| Protection class | IP 68 (up to 10 bar) / IP 69 |
| Entry thread (G) | M12x1.5 |
| Clamping range min. | 5.0 mm |
| Clamping range max. | 6.5 mm |
| Wrench size | 15 mm |
| Dimension (H) | 57 mm |
| Thread length (L) | 5 mm |
| Dispatch | 10 |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

Available on request:

- Short entry thread with short one-piece or two-piece sealing insert.
- Long entry thread with short or full-length insulating one-piece or two-piece sealing insert.