

## Cable glands Progress® EMC nickel-plated brass with contact sleeve



### Long entry thread metric

#### Type approval: Progress MS EMV

- One-piece sealing insert
- not overall length insulated

|                       |  |
|-----------------------|--|
| Article no:           | <b>1180.17.100</b>   |
| E-No:                 | 121032318  |
| EAN:                  | 7611614114958  |
| Material              | Nickel-plated brass  |
| Contact sleeve        | Nickel-plated brass  |
| Seal                  | TPE  |
| O-ring                | NBR  |
| Operation temperature | -40°C / +100°C   |
| Strain relief         | Version A acc. to EN 62444   |
| Protection class      | IP 68 (up to 10 bar) / IP 69   |
| NEMA Type rating      | 4X   |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread          | M16x1.5  |
| Clamping range min.   | 8.0 mm   |
| Clamping range max.   | 10.0 mm  |
| Wrench size           | 18 mm  |
| Dimension H           | 25 mm  |
| Thread length L       | 10 mm  |
| Dispatch              | 50   |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.