


## Synthetic cable glands Syntec® with lamellar technology



### Short entry thread metric

#### Type approval: SYNTEC

- Black RAL 9005
- One-piece sealing ring

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Article no:           | 1545.25.17                                                           |
| E-No:                 | 121754718                                                            |
| EAN:                  | 7611614230535                                                        |
| Material              | Polyamide PA 6                                                       |
| Properties            | halogen-free, black UV resistant (tested according to EN ISO 4892-2) |
| Sealing ring          | TPE or CR (Neoprene)                                                 |
| Operation temperature | -30°C / +100°C                                                       |
| Strain relief         | Version A acc. to EN 62444                                           |
| Protection class      | IP 68                                                                |
| NEMA Type rating      | 4X                                                                   |
| Entry thread (G)      | M25x1.5                                                              |
| Clamping range min.   | 10.0 mm                                                              |
| Clamping range max.   | 17.0 mm                                                              |
| Wrench size           | 29 mm                                                                |
| Dimension (H)         | 38 mm                                                                |
| Thread length (L)     | 10 mm                                                                |
| UL - clamping range   | 12.8-17.0 mm                                                         |
| Dispatch              | 25                                                                   |