

# Synthetic Syntec® cable glands with lamellar technology and anti-kink nozzle



## Long entry thread metric

### Type approval: SYNTEC mit Knickschutz

- Black RAL 9005
- One-piece sealing ring

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Article no:           | 1546.17.1.08                                                         |
| E-No:                 | 121794529                                                            |
| EAN:                  | 7611614079042                                                        |
| Material              | Polyamide PA 6                                                       |
| Properties            | halogen-free, black UV resistant (tested according to EN ISO 4892-2) |
| Sealing ring          | CR (neoprene)                                                        |
| Operation temperature | -30°C / +100°C                                                       |
| Strain relief         | Version A acc. to EN 62444                                           |
| Protection class      | IP 68                                                                |
| NEMA Type rating      | 4X                                                                   |
| Entry thread (G)      | M16x1.5                                                              |
| Clamping range min.   | 4.0 mm                                                               |
| Clamping range max.   | 8.0 mm                                                               |
| Wrench size           | 19 mm                                                                |
| Dimension (H)         | 64 mm                                                                |
| Thread length (L)     | 12 mm                                                                |
| UL - clamping range   | 8.0-8.0 mm                                                           |
| Dispatch              | 50                                                                   |