


Multi Cable Entry MCE EMC



Milled aluminium, one-piece system

- Powerful and safe clamping shield due to spring contact system
- Low transfer impedance
- Absolute process safety with regard to system assembly, full installation control with regard to screen
- High tightness IP6X / IPX8 / IPX9K according to EN62444
- Flexibility in the clamping area due to multiLAYER sealing units
- High pull-out forces according to EN 62444
- Extremely robust (impact resistance)
- No auxiliary materials and lubricants necessary



Article no:	1908.88.03.83.113
E-No:	121810128
EAN:	7611614467573
Material	Alu anodised / galvanised
O-ring	NBR
Flat gasket	NBR (acrylonitrile butadiene rubber)
Operation temperature	-30°C / +105°C
Strain relief	Version to EN 62444
Protection class	IP68 (max. 4 bar during 60 minutes)
Number of executions	3
Clamping range without insert min.	10.0 mm
Clamping range without insert max.	22.5 mm
Shield braid min.	14.0 mm
Shield braid max.	21.0 mm
Dimension A	148 mm
Dimension B	79 mm
Dimension C	26 mm
Drillhole distance X	130 mm
Drillhole distance Y	32 mm
Fixing bolts	M5
Installation opening	112x50 mm
Dispatch	1