

E3S Connect® building distributor



E3S Connect® building distributor

- Scope of delivery: building distributor including 4x patch cassettes, 4x mounting screws, sealing material, moisture absorber

Article no:	4240001
EAN:	4013456582101
Length	380 mm
Width	220 mm
Height	130 mm
Certificate	GHMT Channel Link (z7479a-22 ; c7479a-22)
Network level	4
Installation type	Surface mount
Protection class	IP65 (surface mounting)
Number of fibers	16
Patch cassettes amount	4
Patch cassette assembly max.	8
Connector quantity	4
Connector version	LC/APC Quad
atene KOM released	No
Colour	grey - RAL 7035
Halogen-free	Yes
Loop length (patch cassette)	250 mm
Bending radius (patch cassette)	30 mm
Connector holder	SC DX / LC QD
Entry cable/duct	2
Cable/duct entry Ø	4,5 - 8,3 mm
Cable/duct output quantity	16
Cable/duct output Ø	5,5 - 10 mm
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C

The innovative product design of the E3S Connect® building distributor is suitable for use with E3S Connect system cables to set up a fibre-based building infrastructure. The installation-friendly product design allows simple, fast and therefore time-saving assembly. The E3S Connect® system is based on purely pluggable components; splicing work is not necessary with this system!

- Flexibility for managing fibre-based building networks
- Plug & Play installation
- Flexibility for the in-house concept