


## Complete conduit gland nickel-plated brass



UK  
PA

### Complete conduit gland nickel-plated brass

- Conduit gland US-M
- SPR-AS, SPR-VA / FLEXAgraff-AS

|                       |                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5010.327.050</b>                                                                                                               |
| E-No:                 | 126464940                                                                                                                         |
| EAN:                  | 7611614118611                                                                                                                     |
| Material              | Nickel-plated brass                                                                                                               |
| Bushing               | Nickel-plated brass                                                                                                               |
| Sealing ring          | TPE                                                                                                                               |
| O-ring                | NBR                                                                                                                               |
| Properties            | Highly watertight and dustproof, friction locking of conduit and gland, covered conduit ends, resistant to stretch and vibrations |
| Protection class      | IP 40                                                                                                                             |
| Operation temperature | -40°C / +125°C                                                                                                                    |
| Outer diameter        | 56 mm                                                                                                                             |
| Entry thread          | M50x1.5                                                                                                                           |
| Diameter Ø I          | 45.0 mm                                                                                                                           |
| Diameter Ø B          | 70 mm                                                                                                                             |
| Dimension C           | 14 mm                                                                                                                             |
| Dimension D           | 49 mm                                                                                                                             |
| Wrench size           | 63/66 mm                                                                                                                          |
| Dispatch              | 10                                                                                                                                |

1 = For FLEXAgraff-AS

The reliability is only guaranteed with the corresponding stabilizing bush