

## Complete conduit gland nickel-plated brass



UK  
PA

### Complete conduit gland nickel-plated brass

- Conduit gland US-M
- AIRflex-KUW-PU-AS / -KUW-PVC-AS / -GRS

|                       |                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5010.330.020</b>                                                                                                               |
| E-No:                 | 126464580                                                                                                                         |
| EAN:                  | 7611614118932                                                                                                                     |
| Material              | Nickel-plated brass                                                                                                               |
| Bushing               | Polypropylene                                                                                                                     |
| Sealing ring          | TPE                                                                                                                               |
| O-ring                | NBR                                                                                                                               |
| Properties            | Highly watertight and dustproof, friction locking of conduit and gland, covered conduit ends, resistant to stretch and vibrations |
| Protection class      | IP 54                                                                                                                             |
| Operation temperature | -40°C / +125°C                                                                                                                    |
| Outer diameter        | 21 mm                                                                                                                             |
| Entry thread (G)      | M20x1.5                                                                                                                           |
| Diameter Ø I          | 14.5 mm                                                                                                                           |
| Diameter Ø B          | 27 mm                                                                                                                             |
| Dimension C           | 10 mm                                                                                                                             |
| Dimension D           | 33 mm                                                                                                                             |
| Wrench size           | 23/25 mm                                                                                                                          |
| Dispatch              | 50                                                                                                                                |

The reliability is only guaranteed with the corresponding stabilizing bush