

## EMC conduit gland for metal conduit SPR / FLEXAgraff



UK  
CA

### Complete EMC conduit connectors nickel-plated brass

- Conduit gland US-M
- for FLEXAgraff-CU-AS / SPR-EDU-AS
- with brass thrust collar

|                          |                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>       | <b>5011.328.050</b>                                                                                                                                |
| EAN:                     | 7611614119144                                                                                                                                      |
| Material                 | Nickel-plated brass                                                                                                                                |
| Bushing                  | Polished brass                                                                                                                                     |
| Thrust collar            | Polished brass                                                                                                                                     |
| O-ring                   | NBR                                                                                                                                                |
| Properties               | Highly watertight and dustproof, friction locking of conduit and gland, proper earthing, covered conduit ends, resistant to stretch and vibrations |
| Protection class         | IP 40                                                                                                                                              |
| Operation temperature    | -40°C / +250°C                                                                                                                                     |
| Outer diameter           | 56 mm                                                                                                                                              |
| Entry thread             | M50x1.5                                                                                                                                            |
| Diameter $\varnothing I$ | 45.0 mm                                                                                                                                            |
| Diameter $\varnothing B$ | 70 mm                                                                                                                                              |
| Dimension C              | 14 mm                                                                                                                                              |
| Dimension D              | 49 mm                                                                                                                                              |
| Wrench size              | 63/66 mm                                                                                                                                           |
| Dispatch                 | 10                                                                                                                                                 |

1 = For SPR-EDU-AS

The reliability is only guaranteed with the corresponding stabilizing bush