

## Synthetic straight conduit connector



### Synthetic straight conduit connector

- Quick connector RQG-P
- Black

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5020.027.202R</b>                                                                                                      |
| E-No:                 | 126683019                                                                                                                 |
| EAN:                  | 7611614005027                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | TPE                                                                                                                       |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Application           | Direct reduction / enlarging fitting                                                                                      |
| Protection class      | IP 68 / IP 69                                                                                                             |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 10.0 mm                                                                                                                   |
| Entry thread (G)      | Pg 9                                                                                                                      |
| Diameter Ø I          | 7.0 mm                                                                                                                    |
| Diameter Ø B          | 18.5 mm                                                                                                                   |
| Dimension C           | 10 mm                                                                                                                     |
| Dimension D           | 32.5 mm                                                                                                                   |
| Wrench size           | 16 mm                                                                                                                     |
| Dispatch              | 50                                                                                                                        |

#### Available on request:

- Executions with CTG or NPT entry thread