


## Synthetic conduit connector elbow 90°



EN 45545-2

HL 2



### Synthetic conduit connector elbow 90°

- Quick connector RQW-M
- Black

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5020.036.216</b>                                                                                                       |
| E-No:                 | 126810400                                                                                                                 |
| EAN:                  | 7611614094878                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | TPE                                                                                                                       |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Protection class      | IP 68 / IP 69                                                                                                             |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 13.0 mm                                                                                                                   |
| Entry thread (G)      | M16x1.5                                                                                                                   |
| Diameter Ø I          | 12.0 mm                                                                                                                   |
| Diameter Ø B          | 20.0 mm                                                                                                                   |
| Dimension C           | 12.0 mm                                                                                                                   |
| Dimension E           | 36.0 mm                                                                                                                   |
| Dimension F           | 36.5 mm                                                                                                                   |
| Diameter D            | 20.0 mm                                                                                                                   |
| Dispatch              | 50                                                                                                                        |

#### Available on request:

- Executions with CTG or NPT entry thread