


## Synthetic conduit connector elbow 90°



### Synthetic conduit connector elbow 90°, conically sealing

- Quick connector RQW1-M
- Black

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5020.051.210</b>                                                                                                       |
| E-No:                 | 126812200                                                                                                                 |
| EAN:                  | 7611614095677                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | Conically sealing connection                                                                                              |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Protection class      | IP 66                                                                                                                     |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 10.0 mm                                                                                                                   |
| Entry thread          | M10x1.0                                                                                                                   |
| Diameter Ø I          | 6.0 mm                                                                                                                    |
| Diameter Ø B          | 17.0 mm                                                                                                                   |
| Dimension C           | 12.0 mm                                                                                                                   |
| Dimension E           | 33.5 mm                                                                                                                   |
| Dimension F           | 34.0 mm                                                                                                                   |
| Diameter D            | 16.0 mm                                                                                                                   |
| Dispatch              | 50                                                                                                                        |

#### Available on request:

- Executions with NPT entry thread