


## Conduit glands for Airflex conduit



### Synthetic straight conduit connector

- Synthetic conduit connector USK-P
- Airflex-KUW-PU-AS / -KUW-PVC-AS / -GRS

|                       |                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5020.130.009</b>                                                                                                               |
| EAN:                  | 7611614158716                                                                                                                     |
| Material              | Polypropylene impact-resistant                                                                                                    |
| Bushing               | Polypropylene                                                                                                                     |
| Sealing ring          | TPE                                                                                                                               |
| Properties            | Highly watertight and dustproof, friction locking of conduit and gland, covered conduit ends, resistant to stretch and vibrations |
| Protection class      | IP 54                                                                                                                             |
| Operation temperature | -10°C / +110°C                                                                                                                    |
| Outer diameter        | 14 mm                                                                                                                             |
| Entry thread (G)      | Pg 9                                                                                                                              |
| Diameter Ø I          | 9.0 mm                                                                                                                            |
| Diameter Ø B          | 25 mm                                                                                                                             |
| Dimension C           | 10 mm                                                                                                                             |
| Dimension D           | 41 mm                                                                                                                             |
| Wrench size           | 21/23 mm                                                                                                                          |
| Dispatch              | 50                                                                                                                                |

The reliability is only guaranteed with the corresponding stabilizing bush