

## System equipment carrier



## Knock-in dowel for system equipment carrier

- Building materials: Concrete, Hollow block made from lightweight concrete, Vertically perforated brick, Perforated sand-lime brick, Solid sand-lime brick, Natural stone with dense structure, Solid block made from lightweight concrete, Solid brick

|                            |               |
|----------------------------|---------------|
| <b>Article no:</b>         | <b>507424</b> |
| E-No:                      | 165152300     |
| EAN:                       | 7611614269412 |
| min. hole depth            | 60 mm         |
| Drill Ø                    | 8 mm          |
| Length                     | 230 mm        |
| for insulation thicknesses | 200-240 mm    |
| Dispatch                   | 10            |

Modular support for securely attaching electrical installations in or to heat-insulating external facades. Stable attachment of external lights, sockets, motion detectors, external temperature sensors, radio receivers, anemometers, cameras, letter boxes and much more.

- compatible with Feller SNAPFIX®
- Quick fastening with screw-in wall-plug\_x000D\_
- 2 Produkttypen ermöglichen 6 Anwendungen
- In 10 mm-Schritten an Dämmstärke anpassbar - Zuschneiden entfällt
- Prevents heat bridges
- für Dämmstärken von 160 bis 310 mm
- Can be attached on surfaces made of concrete, bricks, wood, OSB, MDF, gypsum fibreboard etc.
- Easy disassembly

