


## Synthetic conduit connector 45° bend



### Synthetic conduit connector 45° bend

- Quick connector RQB45-M
- Black

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>5100.042.240</b>                                                                                                       |
| E-No:                 | 126821801                                                                                                                 |
| EAN:                  | 7611614158358                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | TPE                                                                                                                       |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Protection class      | IP 68 / IP 69                                                                                                             |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 42.5 mm                                                                                                                   |
| Entry thread          | M40x1.5                                                                                                                   |
| Diameter Ø I          | 31.5 mm                                                                                                                   |
| Diameter Ø B          | 52.0 mm                                                                                                                   |
| Dimension C           | 17.0 mm                                                                                                                   |
| Dimension E           | 82.5 mm                                                                                                                   |
| Dimension F           | 86.0 mm                                                                                                                   |
| Wrench size           | 48 mm                                                                                                                     |
| Dispatch              | 10                                                                                                                        |

#### Available on request:

- Executions with NPT entry thread