


## Synthetic conduit connector distributor body



EN 45545-2

HL 2



### Synthetic conduit connector quick coupling

- Quick connector RQK-PA
- Black

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Article no:           | 5602.028.228                                                                                                              |
| E-No:                 | 126863600                                                                                                                 |
| EAN:                  | 7611614200576                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | TPE                                                                                                                       |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Protection class      | IP 68 / IP 69                                                                                                             |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 28.5 mm                                                                                                                   |
| Outer diameter 2      | 28.5 mm                                                                                                                   |
| Diameter Ø B          | 37.0 mm                                                                                                                   |
| Diameter Ø I          | 23.5 mm                                                                                                                   |
| Dimension D           | 86.5 mm                                                                                                                   |
| Dispatch              | 10                                                                                                                        |