

## Synthetic locking plugs for increased safety Ex e II



### Entry thread Pg

- Black RAL 9005
- with O-ring

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>8841.13</b>                                    |
| EAN:                  | 7611614060231                                     |
| Material              | Polyamide glass fiber reinforced                  |
| O-ring                | NBR                                               |
| Operation temperature | -20°C / +90°C                                     |
| Protection class      | IP 68 (up to 10 bar) / IP 69                      |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex e IIC Gb                                 |
| Dust                  | II 1D Ex ta IIIC Ga                               |
| Zone                  | Gas 2 / dust 21                                   |
| Certificate           | DMT 03 ATEX E 049                                 |
| IECEx Certificate     | IECEx BVS 07.0021                                 |
| Entry thread (G)      | Pg 13                                             |
| Wrench size           | 24 mm                                             |
| Imbus wrench size     | 8                                                 |
| Dimension (H)         | 14.5 mm                                           |
| Thread length (L)     | 9.0 mm                                            |
| Dispatch              | 100                                               |