

## ThermoX® installation housing



**LUFTDICHT**

### ThermoX® universal housing with mineral fibreboard

- saves time - no plastering; close joint gap if necessary
- ceiling exit (CE) up to Ø 86 mm possible
- Heat distortion resistant to 220°C
- max. installation height for low-voltage luminaire 65 mm, HV luminaire 70 mm
- lamp wattage LV: max. 35 W with AL reflector / 20 W Cool-Beam
- lamp power for HV luminaires max. 35 W with AL reflector (base GU 10) / 20 W Cool-Beam
- max. LED lamp output 6.6 W

<b>Article no:</b>	<b>9300-22</b>
E-No:	920840009
EAN:	4013456470347
For panel thickness	7 - 40 mm
Depth	90 mm
Ceiling exit (CE) Ø	0-86 mm
installation from front, cut hole Ø	120 mm
Dispatch	10

ThermoX® installation housing for installing halogen and pivoting recessed LED luminaires in various ceiling structures. The housing protects the surrounding material (moisture barrier foil, insulation etc.) from the lamp's extreme operating temperatures and creates an air-tight closure.

- Installation housing for halogen luminaires (low voltage and high voltage)
- Fire-preventive and air-tight
- For insulated hollow ceilings
- Two different front part types
- Integrated transformer closing cap
- Ceiling exits (CE) up to Ø 86 mm
- Installation from either above or below

