Fire-stop box FlamoX®





 made of galvanised sheet metal with lining made of fire-resistant coating 	
Article no:	9435-03
E-No:	920848209
EAN:	4013456546080
For panel thickness	2 x 12,5 mm
Length	320 mm
Width	270 mm
Height	150 mm
Installation height	200 mm
Exit opening Ø	180 mm
Max. luminaire or loudspeaker installation height	150 mm
Tube entries up to M25	2
Cable entries up to Ø 13.5 mm	2
LED luminaires	34 Watt
Halogen luminaires	75 Watt
DIBt approval	Z-19.53-2603
ETA approval	ETA-20/0238
Halogen-free	Yes
Dispatch	1

Fire-protection housing FlamoX®, 320x270x150 mm

· for luminaires and loudspeakers Smokeproof and halogen-free · for fire loads from above and below

FlamoX® installation housings for luminaires and loudspeakers protect lives and material goods if a fire breaks out. In luminaire and loudspeaker installations in fire-protection ceilings, the integrated fire-retardant coating gives the housings the fire-protection class F30 (EI30) of the ceiling. They prevent fire and flue gases from spreading, so they secure escape routes in buildings. FlamoX® fire-protection housings provide certified security.

- Safe, certified fire-protection housings for built-in luminaires and loudspeakers
- · Fast, easy fitting from the underside of the ceiling
- Suitable for fire resistance from above and below
- · Installation without additional suspension
- $\cdot \,$ No use of additional fire protection materials or sealing compounds



