## Box sealing system DS 90 / 74 mm



## Box sealing system DS 90 / 74 mm

- · for EI90 fire-protection walls
- · for wall entries and feed-throughs
- · attachment using tried-and-tested FX metal plate screws
- with integrated sealing inserts
- · ensures smoke-tight room separation (seals against cold smoke)
- · unlimited building material shelf life

Article no:	9459-03
E-No:	121819008
EAN:	4013456536289
Cut hole Ø	74 mm
Min. wall thickness	100 mm
Cable entries	Maximum population (internal diameter 40 mm)
DIBt approval	Z-19.53-2189
· · · · · ·	
for sound insulation walls up to	77 dB
for sound insulation walls up to Packaging inner/dispatch	77 dB 10/100

The box sealing system DS 90 / 74 mm for cables, cable bundles and conduits. The fire-proof and smoke-proof box sealing is quick and easy to install and can also be retrofitted on cables and conduits. The easy-to-fit product offers certified safety and ensures the fire resistance class of the wall (EI30-EI90).

- · Secure, visible, certified fire sealings
- · For wall feed-throughs and entries
- · Automatic sealing of the joints and gaps between cables no filling and smoothing
- · Non-destructive retrofitting
- · For cable bundles or individual installation conduits



