

## Fire protection cavity wall box



### Quickbox® HWD 90 3x1

- compatible with Feller SNAPFIX®
- for F30-F90 or EI30-EI90 fire-protection walls
- VKF approval 21042
- also for opposing installation
- for plate thickness >10 - 40 mm
- matching plug-in cover for Art. No. 9498-77 New Look one Art. No. 9919.10
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm



Article no:	9498-77.03
E-No:	155014029
EAN:	7611614240671
Length	205 mm
Width	83 mm
Depth	50 mm
Cut hole Ø	83 mm
Combination	3x1
Dispatch	5

HWD 90 cavity wall boxes for EI30-EI90 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 90 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- compatible with Feller SNAPFIX®
- For fire-protection walls F30-F90 or EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- Also for directly opposing installation
- May not be used inside encapsulated walls

does not match with the following types:  
Prestige model by Feller Edizio Due

