


Fire protection cavity wall box



Quickbox® Maxi HWD 90 2x2

- compatible with Feller SNAPFIX®
- for F30-F90 or EI30-EI90 fire-protection walls
- VKF Approval 26831
- also for opposing installation
- for plate thickness >10 - 40 mm
- matching plug-in cover for Art. No. 9498-77 New Look one Art. No. 9919.10
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- Pipes must be sealed with sealing plugs on both sides of the pipes!



Article no:	9499-77.04
E-No:	372632709
EAN:	7611614276816
Length	145 mm
Width	145 mm
Depth	73.5 mm
Cut hole Ø	83 mm
Tube entries up to M25	4
Combination	2x2
Dispatch	5

HWD 90 cavity wall boxes for EI30-EI90 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 90 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- compatible with Feller SNAPFIX®
- For fire-protection walls F30-F90 or EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- Also for directly opposing installation
- May not be used inside encapsulated walls

does not match with the following types:
Prestige model by Feller Edizio Due

