SOUND INSULATION BOX



& 850 °C

CE

Quickbox® Maxi 2x2

- · compatible with Feller SNAPFIX®
- One-gang boxes for sound insulation walls in buildings
- $\cdot\,$ Maintains the wall's sound insulation protection
- also for opposing installation
- $\cdot~$ for plate thickness >10 40 mm
- · For device screws Ø 3 mm
- $\cdot\,$ Max. tightening torque 0.5 Nm
- · Pipes must be sealed with sealing plugs on both sides of the pipes!

Article no:	9799-77.04
E-No:	372632209
EAN:	7611614276915
Combination	2x2
Cut hole Ø	83 mm
Tube entries up to M25	4
Length	145 mm
Width	145 mm
Depth	73.5 mm
Dispatch	5

Sound insulation box for use in walls with increased demands on sound protection. The solid box body with additional sound insulation sheathing absorbs and reflects sound, which prevents disturbances in adjacent rooms. Sound insulation is the same as if no installation boxes were installed.

- · compatible with Feller SNAPFIX®
- · Tube entries up to M25
- · Maintains the wall's sound insulation protection
- $\cdot \,$ also for opposing installation
- Retrofitting is possible
- Installation up to 3x2 combination

does not match with the following types: Prestige model by Feller Edizio Due



