

## AGRO Flush-mounted box for equipment



### Flush-mounted box 4x3

- Nail domes also serve as Prefix® connection points
- Increased stability
- Separately guided nailing points
- With separator wall and stabilisation lid
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- compatible with Feller SNAPFIX®

<b>Article no:</b>	<b>9902.12</b>
E-No:	372118439
EAN:	7611614329949
Length	257 mm
Width	197 mm
Depth	70 mm
Conduit entries M20	8
Conduit entries M25	8
Combination	4x3
Combination conduit entries M20/25	4
Drilling Center max. Ø 40 mm	6
Dispatch	8

The new wiring boxes for concrete and masonry walls offer even more space for the installation and wiring of actuators, WLAN modules and terminals. Using the new Prefix® mounting system, wing brackets for connection to opposing formwork can be attached directly to the nail channels on the box perimeter – a unique feature on the market. The nails no longer need to be disconnected / snipped thanks to the external nail points. The protective cover remains on the box and protects the connection holes from dirt. The special bristle arrangement makes it possible to keep track of box size in the wall, even with a thick coat of plaster.

- compatible with Feller SNAPFIX®
- Wing bracket connection via the existing nail channels on the box's perimeter
- Suitable for exposed concrete
- Protective cover with new marking bristles for easy identification of box dimensions
- Separately routed nail channels prevent box displacements
- Improved stabilization walls for safe separation of circuits
- Covering of the fixing holes by protective cover - even after stripping the formwork

