

AGRO flush-mounted box with glow wire test 850°C



AGRO flush-mounted box 2x1

- compatible with Feller SNAPFIX®
- New with strap attachment
- Increased installation volumes
- Simple alignment
- Separator wall for electrical circuit separation
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm

| | |
|------------------------------------|--------------------|
| Article no: | 9902.22.850 |
| E-No: | 372633219 |
| EAN: | 7611614330020 |
| Combination | 2x1 |
| Length | 130.5 mm |
| Width | 70.5 mm |
| Depth | 66 mm |
| Conduit entries M20 | 6 |
| Conduit entries M25 | 6 |
| Combination conduit entries M20/25 | 2 |
| Dispatch | 50 |

The new lightweight boxes offer even more space for installation and wiring of actuators, WLAN modules and terminals.

Thanks to the additional lugs, the flush-mounted box can now also be installed in panelling/sheeting without connection to a timber stud. A comprehensive design with webs and stabilization walls increases strength while also facilitating safe separation of circuits.

A marker notch on each side of the box enables it to be easily aligned, both horizontally and vertically.

- compatible with Feller SNAPFIX®
- Additional lug attachment for panelling/sheeting without timber studs
- Increased stability thanks to comprehensive design concept
- Easy alignment using marker notches on each side
- FX4 lug bolts – the fastest screw fastening for flush-mounted boxes in lightweight construction
- Increased installation volumes for wiring