

AGRO flush-mounted box with glow wire test 850°C



AGRO flush-mounted box 3x3

- compatible with Feller SNAPFIX®
- New with strap attachment
- Increased installation volumes
- Simple alignment
- Separator wall for electrical circuit separation
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm

Article no:	9902.29.850
E-No:	372633339
EAN:	7611614330082
Combination	3x3
Length	190.5 mm
Width	190.5 mm
Depth	66 mm
Conduit entries M20	8
Conduit entries M25	8
Combination conduit entries M20/25	4
Drilling Center max. Ø 40 mm	4
Dispatch	8

The new lightweight boxes offer even more space for installation and wiring of actuators, WLAN modules and terminals.

Thanks to the additional lugs, the flush-mounted box can now also be installed in panelling/sheeting without connection to a timber stud. A comprehensive design with webs and stabilization walls increases strength while also facilitating safe separation of circuits.

A marker notch on each side of the box enables it to be easily aligned, both horizontally and vertically.

- compatible with Feller SNAPFIX®
- Additional lug attachment for panelling/sheeting without timber studs
- Increased stability thanks to comprehensive design concept
- Easy alignment using marker notches on each side
- FX4 lug bolts – the fastest screw fastening for flush-mounted boxes in lightweight construction
- Increased installation volumes for wiring