

## Prefix concrete installation socket



### Prefix® concrete construction box 1x1 / Ø 30 mm

- compatible with Feller SNAPFIX®
- Fast and easy installation on opposing formwork without support element and abutment
- Holding in place using the Prefix® installation technology leaves both hands free for securing with tie wires
- Several units can be securely joined together to form norm-compliant combinations
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm



|                    |               |
|--------------------|---------------|
| <b>Article no:</b> | <b>9940</b>   |
| E-No:              | 372711309     |
| EAN:               | 7611614251127 |
| Exit opening Ø     | 30 mm         |
| Depth              | 97 mm         |
| Combination        | 1x1           |
| Dispatch           | 10            |

Inlet box with Prefix® installation technology, for quick and easy installation against subsequently placed front formwork - without separate supporting element. Thanks to its spring-loaded wing brackets, this one-piece socket with two integrated front parts can be installed in such a way that its front surface will be pressed hard against the front formwork when it is subsequently placed, ensuring the socket will sit just right against the formwork and resulting in a smooth, clean finish after concreting.

- compatible with Feller SNAPFIX®
- Easy and quick installation
- Pre-fixing by means of B<sup>1</sup> Prefix® installation technology
- For exposed concrete
- Can be combined

