

Fibre management plate (FMP) - Cable/conduit break-out opening Ø 3,0 – 8,0



Fibre management plate FMP, 192 fibres, CSP, 24 outlets, loop

- 24 hybrid entry ports Ø3.0 - 8.0 mm.
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured fibre optic management.
- IP68
- Easy to install.
- Window Cut.
- Scope of delivery: FMP including splice cassettes, 4x mounting screws, sealing material, moisture absorber

| | |
|---|-------------------------------------|
| Article no: | AT29333 |
| EAN: | 8712259387093 |
| Network level | 3 |
| Installation type | Underground |
| Protection class (in supply sleeve) | IP68 |
| Halogen-free | Yes |
| Number of fibers | 192 |
| Number of splice trays | 16 |
| Height of splice trays | 4 mm |
| Cascadable (loop function) | Yes |
| Loop length (splice tray) | 300 |
| Bending radius (splice tray) | 30 mm |
| Splice protection holder | CSP Crimp / Mini heat shrink tubing |
| Entry cable/duct | 24 |
| Cable/duct entry Ø | 4,5 – 8,3 mm |
| Number of cable / conduit breakout openings | 2 |
| Cable / conduit breakout opening Ø | M20/M25 |
| Cable/duct output Ø | 3,0 – 8,0 mm |
| Temperature range storage | -10 °C / +60°C |
| Temperature range installation | -10 °C / +60°C |
| Temperature range during operation | -20 °C / +60°C |
| Length | 380 mm |
| Width | 220 mm |
| Height | 130 mm |
| Colour | Transparent / Grey |

The innovative product design of the splice distribution box is suitable for installation in the underground distribution point supply sleeve (AT29030). The installation-friendly product design allows simple, fast and thus time-saving assembly.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTX concept.