

Building distributor (Gf-GV) - Cable/conduit break-out opening Ø 3,0 – 8,0 m



Building distributor Gf-GV, 96 fibres, CSP, 48 outlets, IP65

- 48 hybrid entry ports Ø 3,0 - 8,0 mm.
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured management of cables, fibres and welding protectors.
- Suitable for direct buried customer cables and ducts
- Easy to install.
- Save on working time
- IP65 Waterproof
- Impact-resistant
- Scope of delivery: FMB including splice cassettes, 4x mounting screws, sealing material, mounting bracket

| | |
|---|-------------------------------------|
| Article no: | AT29362 |
| EAN: | 8712259363561 |
| Network level | 4 |
| Installation type | Surface mount |
| Protection class | IP65 |
| Halogen-free | Yes |
| Number of fibers | 96 |
| Number of splice trays | 8 |
| Height of splice trays | 8 mm |
| Cascadable (loop function) | No |
| Loop length (splice tray) | 300 |
| Bending radius (splice tray) | 30 mm |
| Splice protection holder | CSP Crimp / Mini heat shrink tubing |
| Entry cable/duct | 2 |
| Cable/duct entry Ø | 4,5 – 8,3 mm |
| Number of cable / conduit breakout openings | 1 |
| Cable / conduit breakout opening Ø | M12 / 16 / 20 / 25 |
| Cable/duct output quantity | 48 |
| Cable/duct output Ø | 3,0 – 8,0 mm |
| Temperature range storage | -10 °C / +60°C |
| Temperature range installation | -10 °C / +60°C |
| Temperature range during operation | -20 °C / +60°C |
| Length | 380 mm |
| Width | 220 mm |
| Height | 130 mm |
| Colour | Transparent / Grey |

The splice distributor box can be used as a surface-mounted building distributor with the help of the mounting device and cover if required. The splice distributor box with cover (FMB) has protection class IP65 and is protected against dust and water ingress.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTX concept.