

Building distributor (Gf-GV) - Cable/conduit break-out opening Ø 3,0 – 8,0 m



Building distributor Gf-GV,192 fibres, CSP, 48 outlets, IP65

- 48 hybrid entry ports Ø 3,0 - 8,0 mm.
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured management of cables, fibres and welding protectors.
- Suitable for direct buried customer cables and ducts
- Easy to install.
- Save on working time
- IP65 Waterproof
- Impact-resistant
- Scope of delivery: FMB including splice cassettes, 4x mounting screws, sealing material, mounting bracket

Article no:	AT29363
EAN:	8712259375335
Network level	4
Installation type	Surface mount
Protection class	IP65
Halogen-free	Yes
Number of fibers	192
Number of splice trays	16
Height of splice trays	4 mm
Cascadable (loop function)	No
Loop length (splice tray)	300
Bending radius (splice tray)	30 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Entry cable/duct	2
Cable/duct entry Ø	4,5 – 8,3 mm
Number of cable / conduit breakout openings	1
Cable / conduit breakout opening Ø	M12 / 16 / 20 / 25
Cable/duct output quantity	48
Cable/duct output Ø	3,0 – 8,0 mm
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C
Length	380 mm
Width	220 mm
Height	130 mm
Colour	Transparent / Grey

The splice distributor box can be used as a surface-mounted building distributor with the help of the mounting device and cover if required. The splice distributor box with cover (FMB) has protection class IP65 and is protected against dust and water ingress.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTX concept.