

Distribution boxes for light controls. AK2 DALI.



Pluggable AK2 front part, Wieland GST18, out: 3x5pin DALI blue

- For DALI controlled lighting.
- Equipped with VD wire 2.5 mm².
- All connectors are equipped with locking.
- Wieland gesis® CLASSIC GST18® snap-in connector
- 5-pin for DALI applications
- Connectors are self-locking, can be released with tools
- Prefabricated with halogen-free connection wires 2.5 mm².

| | |
|---------------------|---------------------|
| Article no: | AT6328 |
| E-No: | 127917319 |
| EAN: | 8712259299990 |
| Length | 125 mm |
| Width | 100 mm |
| Depth | 42 mm |
| Incoming connection | 5 pole |
| Outgoing connector | 3 x 5 poles, blue |
| Pre-wiring | 2,5 mm ² |
| Protection class | IP20 |
| Mounting type | Snap on |
| Colour | grey - RAL 7035 |
| Halogen-free | Yes |
| Dispatch | 10 |

The front parts of the AK2 DALI series offer solutions when lighting control in building installation technology is implemented using the DALI standard. Just as the lighting components have a DALI interface, the front parts are equipped with DALI connectors. This means that the AK2 modular system can be used to implement flexible applications in building automation, for example to quickly and easily wire and individually control groups of luminaires.