

## Distribution boxes for light controls. AK2 DALI.



### Pluggable AK2 front part, WAGO WINSTA® MIDI, out: 4x5pin DALI blue

- For DALI controlled lighting.
- Equipped with VD wire 2.5 mm<sup>2</sup>.
- All connectors are equipped with locking.
- WAGO WINSTA® MIDI snap-in connector
- 5-pin for DALI applications
- Connectors are self-locking, can be released with tools
- Prefabricated with halogen-free connection wires 2.5 mm<sup>2</sup>.

<b>Article no:</b>	<b>AT7752</b>
E-No:	127917369
EAN:	8712259355610
Length	125 mm
Width	100 mm
Depth	42 mm
Incoming connection	5 pole
Outgoing connector	4 x 5 poles, blue
Pre-wiring	2,5 mm <sup>2</sup>
Protection class	IP20
Mounting type	Snap on
Colour	grey - RAL 7035
Halogen-free	Yes
Dispatch	10

The front parts of the AK2 DALI series offer solutions when lighting control in building installation technology is implemented using the DALI standard. Just as the lighting components have a DALI interface, the front parts are equipped with DALI connectors. This means that the AK2 modular system can be used to implement flexible applications in building automation, for example to quickly and easily wire and individually control groups of luminaires.