

## AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve in

**Short entry thread Pg****Type approval: Progress MS EMC EX**

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>EX1080.21.190</b>                                                                                               |
| EAN:                  | 7611614178691                                                                                                      |
| Material              | Nickel-plated brass                                                                                                |
| Seal                  | TPE                                                                                                                |
| O-ring                | FPM                                                                                                                |
| Operation temperature | -60°C / +100°C                                                                                                     |
| Protection class      | IP 66 / IP 68 (up to 10 bar)                                                                                       |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31                                                                  |
| Gas                   | II 2G Ex eb IIC Gb                                                                                                 |
| Dust                  | II 2D Ex tb IIIC Db                                                                                                |
| Zone                  | Gas 1 and 2 / dust 21 and 22                                                                                       |
| Certificate           | SEV 15 ATEX 0152X                                                                                                  |
| IECEx Certificate     | IECEx SEV 15.0019X                                                                                                 |
| CCC Certificate       | CCC 2022322313004811                                                                                               |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread (G)      | Pg 21                                                                                                              |
| Clamping range min.   | 17.0 mm                                                                                                            |
| Clamping range max.   | 19.0 mm                                                                                                            |
| Wrench size           | 30 mm                                                                                                              |
| Dimension (H)         | 33 mm                                                                                                              |
| Thread length (L)     | 7.5 mm                                                                                                             |
| Dispatch              | 25                                                                                                                 |

Long entry thread available on request