

AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve in



Short entry thread metric

Type approval: Progress MS EMC EX

- One-piece sealing insert
- not overall length insulated

Article no:	EX1080.32.210
E-No:	121393708
EAN:	7611614178103
Material	Nickel-plated brass
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68 (up to 10 bar)
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEx Certificate	IECEx SEV 15.0019X
CCC Certificate	CCC 2022322313004811
Properties	Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland
Entry thread (G)	M32x1.5
Clamping range min.	17.0 mm
Clamping range max.	21.0 mm
Wrench size	36 mm
Dimension (H)	32 mm
Thread length (L)	8 mm
Dispatch	25

1 = Metric coarse-pitch thread (with VDE test report)

Long entry thread available on request