

# AGRO synthetic cable glands Progress® GFK increased safety Ex e II



## Entry thread metric

### Type approval: Progress GFK EX

- Light grey RAL 7035
- One-piece sealing insert

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>EX1571.40.330</b>                              |
| E-No:                 | 121760838                                         |
| EAN:                  | 7611614176079                                     |
| Material              | Polyamide glass fiber reinforced                  |
| Properties            | halogen-free                                      |
| Seal                  | TPE / NBR                                         |
| Operation temperature | -20°C / +85°C                                     |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Zone                  | Gas 1 and 2 / dust 21 and 22                      |
| Certificate           | SEV 15 ATEX 0152X                                 |
| IECEx Certificate     | IECEx SEV 15.0019X                                |
| CCC Certificate       | CCC 2022322313004811                              |
| Entry thread (G)      | M40x1.5                                           |
| Clamping range min.   | 30.0 mm                                           |
| Clamping range max.   | 33.0 mm                                           |
| Wrench size           | 50 mm                                             |
| Dimension (H)         | 40 mm                                             |
| Thread length (L)     | 15 mm                                             |
| Dispatch              | 10                                                |

3 = Material sealing insert NBR