


AGRO combination conduit glands Progress® nickel-plated brass increased safety



AGRO combination conduit glands Progress® nickel-plated brass increased safety Ex e II

Type approval: Progress MS Kombi EX

- One-piece sealing insert
- not overall length insulated

Article no:	EX1700.25.21.160
EAN:	7611614252926
Material	Nickel-plated brass
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEx Certificate	IECEx SEV 15.0019X
CCC Certificate	CCC 2022322313004811
Entry thread	M25x1.5
Outer diameter	21 mm
Clamping range min.	13.0 mm
Clamping range max.	16.0 mm
Wrench size	30/29 mm
Dimension H	43 mm
Thread length L	7 mm
Dispatch	25

Long entry thread available on request

Depending on the type of conduit, the stabilising bush must be ordered separately.

Warning: Only metallic conduits or conduits with metallic braiding may be applied !