


AGRO cable glands Progress® nickel-plated brass with clamps increased safe



Short entry thread metric

Type approval: Progress MS KB EX

- Two-piece sealing insert
- not overall length insulated

Article no:	EX1803.63
E-No:	121396918
EAN:	7611614176642
Material	Nickel-plated brass
Screws	Stainless steel A2
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68 (up to 10 bar)
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Entry thread (G)	M63x1.5
Clamping range with insert min.	40.0 mm
Clamping range with insert max.	46.0 mm
Clamping range without insert min.	46.0 mm
Clamping range without insert max.	52.0 mm
Wrench size	70 mm
Dimension (H)	55 mm
Thread length (L)	10 mm
Additional note	-
Dispatch	5

1 = One-piece sealing insert

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

Available on request:

- Long entry thread
- Executions in steel A2 and A4