


AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve and

**Short entry thread Pg****Type approval: Progress MS EMC KB EX**

- One-piece sealing insert
- not overall length insulated

Article no:	EX1803.80.13.110
EAN:	7611614176956
Material	Nickel-plated brass
Screws	Stainless steel A2
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68 (up to 10 bar)
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Entry thread (G)	Pg 13
Clamping range min.	8.0 mm
Clamping range max.	11.0 mm
Wrench size	24 mm
Dimension (H)	31 mm
Thread length (L)	6 mm
Note	-
Dispatch	50

1 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X_x000D_
Long entry thread available on request