


# AGRO cable glands Ex Compact nickel-plated brass with clamps Ex d IIC and



## Entry thread metric

### Type approval: EX Compact MS KB

- One-piece sealing insert
- not overall length insulated

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| <b>Article no:</b>    | <b>EX1826.25.180</b>                                               |
| E-No:                 | 121472558                                                          |
| EAN:                  | 7611614316154                                                      |
| Material              | Nickel-plated brass                                                |
| Seal                  | NBR                                                                |
| O-ring                | FPM                                                                |
| Operation temperature | -60°C / +105°C                                                     |
| Protection class      | IP 66 / IP 68 (30 bar)                                             |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex db eb IIC Gb                                              |
| Dust                  | II 2D Ex tb IIIC Db                                                |
| Zone                  | Gas 1 and 2 / dust 21 and 22                                       |
| Certificate           | SEV 17 ATEX 0153                                                   |
| IECEx Certificate     | IECEx SEV 17.0017                                                  |
| Entry thread          | M25x1.5                                                            |
| Clamping range min.   | 12.5 mm                                                            |
| Clamping range max.   | 18.0 mm                                                            |
| Wrench size           | 32 mm                                                              |
| Dimension H           | 37 mm                                                              |
| Thread length L       | 12 mm                                                              |
| Dispatch              | 20                                                                 |

### Available on request:

- Entry thread Pg and NPT
- Stainless steel A2 or A4