
Reduction fittings nickel-plated brass increased safety Ex e II







Accessories

Type approval: Reduktion MS EX

- · Outer thread Pg
- \cdot Inner thread metric
- \cdot with O-ring

Article no:	EX3500.11.10
EAN:	7611614175881
Material	Nickel-plated brass
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	ll 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Thread outside	Pg 11
Internal thread	M10x1.5
Additional note	1
Wrench size	21 mm
Dimension (H)	3.0 mm
Dimension L	6 mm
Note	-
Dispatch	50

1 = Metric coarse-pitch thread (with VDE test report)

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

The norm interdicts to screw several reduction/enlarging fittings into each other!



Details subject to change | State 2024-05-03 | agro.ch