

## Reduction fittings nickel-plated brass increased safety Ex e II



### Accessories

#### Type approval: Reduktion MS EX

- Outer thread metric
- Inner thread metric
- with O-ring

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>EX3500.25.20</b>                               |
| E-No:                 | 126340620                                         |
| EAN:                  | 7611614175447                                     |
| Material              | Nickel-plated brass                               |
| O-ring                | FPM                                               |
| Operation temperature | -60°C / +100°C                                    |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Zone                  | Gas 1 and 2 / dust 21 and 22                      |
| Certificate           | SEV 15 ATEX 0151                                  |
| IECEx Certificate     | IECEx SEV 15.0018                                 |
| CCC Certificate       | CCC 2022322313004717                              |
| Thread outside        | M25x1.5                                           |
| Internal thread       | M20x1.5                                           |
| Additional note       | -                                                 |
| Wrench size           | 30 mm                                             |
| Dimension (H)         | 3.5 mm                                            |
| Dimension L           | 7 mm                                              |
| Note                  | -                                                 |
| Dispatch              | 25                                                |

1 = Metric coarse-pitch thread (with VDE test report)

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

The norm interdicts to screw several reduction/enlarging fittings into each other!