

## Reduction fittings nickel-plated brass increased safety Ex e II



### Accessories

#### Type approval: Reduktion MS EX

- Outer thread Pg
- Inner thread metric
- with O-ring

<b>Article no:</b>	<b>EX3500.36.40</b>
EAN:	7611614176048
Material	Nickel-plated brass
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Thread outside	Pg 36
Internal thread	M40x1.5
Additional note	-
Wrench size	50 mm
Dimension (H)	4.5 mm
Dimension L	8 mm
Note	-
Dispatch	10

1 = Metric coarse-pitch thread (with VDE test report)

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

The norm interdicts to screw several reduction/enlarging fittings into each other!