


## Locking plugs nickel-plated brass increased safety Ex e II



### Short entry thread metric

Type approval: Verschlusszapfen MS EX

· with O-ring

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>EX8717.08</b>                                  |
| E-No:                 | 126233400                                         |
| EAN:                  | 7611614175522                                     |
| Material              | Nickel-plated brass                               |
| O-ring                | FPM                                               |
| Operation temperature | -60°C / +100°C                                    |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Zone                  | Gas 1 and 2 / dust 21 and 22                      |
| Certificate           | SEV 15 ATEX 0151                                  |
| IECEx Certificate     | IECEx SEV 15.0018                                 |
| CCC Certificate       | CCC 2022322313004717                              |
| Entry thread (G)      | M16x1.5                                           |
| Diameter              | 19 mm                                             |
| Dimension (H)         | 3 mm                                              |
| Thread length (L)     | 5 mm                                              |
| Dispatch              | 50                                                |

1 = Metric coarse-pitch thread (with VDE test report)

### Available on request:

- Long entry thread
- Executions in steel A2 and A4